

Model	2030A-S
Capacity @ 500 mm LC	3,000 kg
Power Type	Electric
Controller	CURTIS

CLG2030A-S

ELECTRIC FOUR WHEEL
PNEUMATIC TIRE FORKLIFTS



TOUGH WORLD. TOUGH EQUIPMENT.

CLG2030A-S SPECIFICATIONS >>>

General	Model	1			CLG2030A-S
	Power Type	2			Electric
	Base Capacity	3	@ rated load center	kg	3,000
	Load Center	4		mm	500
Weights	Service Weight	5	unloaded with minimum weight battery	kg	4,800
	Axle Load	6	loaded, front / rear	kg	7,085 / 2,299
		7	unloaded, front / rear	kg	715 / 2,501
	Tires	8	Tire Type		Pneumatic
Tires	Wheels	9	front / rear		2 / 2
	Wheelbase	10		mm	1,700
	Tire Size	11	front		28x9-15-14PR
		12	rear		6.5-10-10PR
	Tread Width	13	front / rear		1,005 / 980
Mast	Max. Fork Height	14	with std 2 - stage mast	mm	3,000
	Freelift	15	with std 2 - stage mast	mm	80
	Height, Upright Lowered	16	with std 2 - stage mast	mm	2,085
	Height, Upright Extended	17	with std 2 - stage mast	mm	4145
	Mast Tilt, Fwd / Back	18	with std 2 - stage mast	deg	6° / 12°
		19	width	mm	1,100
	Fork Spread	20	minimum / maximum	mm	272 / 1,072
	Fork Dimensions	21	T x W x L	mm	45 x 122 x 1,070
	Length to Fork Face	22	with std 2 - stage mast	mm	2,565
	Overall Width	23		mm	1,264
Chassis	Overhead Guard Height	24		mm	2,230
	Turning Radius	25	minimum outside	mm	2,300
	Fork Overhang	26	with std 2 - stage mast	mm	475
	Right Angle Stack	27	add load length and clearance	mm	3,975
	Ground Clearance	28	minimum loaded	mm	140
		29	center of wheelbase	mm	155
	Battery Compartment	30	length / width / height	mm	680 / 1,138 / 790
	Travel Speed	31	loaded / unloaded	kph	15 / 15.5
	Lift Speed	32	loaded / unloaded	m/s	0.30 / 0.45
	Lower Speed	33	loaded / unloaded	m/s	0.46 / 0.40
Performance	Max. Drawbar Pull	34	5 min. rating	kg	1,633
		35	60 min. rating	kg	336
	Max. Gradeability	36	5 min. rating	%	15
		37	drive / hydraulic (make, type)		CURTIS, AC
	Controllers	38	drive output (60 min. rating)	kW	12
Systems	Motors	39	hydraulic output (15 min. rating)	kW	14
		40	type		Lead Acid
	Battery	41	voltage		80
		42	max. capacity (6 hour rating)	Ah	500
		43	weight, minimum / maximum	kg	1,440-1,740

